


MCBs technical details

Terminal capacity of S200, S200M, S200MUC, S300P

Rigid cable


Stripping length 10...12mm, max terminal capacity



Conductor terminal			Busbar terminal			
2	x	0,75 mm ²	2	x	0,75 mm ²	or busbar
2	x	1 mm ²	2	x	1 mm ²	or busbar
2	x	1,5 mm ²	2	x	1,5 mm ²	or busbar
2	x	2,5 mm ²	1	x	2,5 mm ²	or busbar
2	x	4 mm ²	1	x	4 mm ²	or busbar
2	x	6 mm ²	1	x	6 mm ²	or busbar
2	x	10 mm ²	1	x	10 mm ²	or busbar
2	x	16 mm ²				busbar
1	x	25 mm ²				busbar
1	x	35 mm ²				busbar

Flexible cable


Stripping length 10...12mm, max terminal capacity



Conductor terminal			Busbar terminal			
2	x	0,75 mm ²	2	x	0,75 mm ²	or busbar
2	x	1 mm ²	2	x	1 mm ²	or busbar
2	x	1,5 mm ²	2	x	1,5 mm ²	or busbar
2	x	2,5 mm ²	1	x	2,5 mm ²	or busbar
2	x	4 mm ²	1	x	4 mm ²	or busbar
2	x	6 mm ²	1	x	6 mm ²	or busbar
2	x	10 mm ²				busbar
1	x	16 mm ²				busbar
1	x	25 mm ²				busbar

Flexible cable with ferrule without collar

Stripping length 10...12mm, max terminal capacity¹



Conductor terminal			Busbar terminal			
2	x	0,75 mm ²	2	x	0,75 mm ²	or busbar
2	x	1 mm ²	2	x	1 mm ²	or busbar
2	x	1,5 mm ²	2	x	1,5 mm ²	or busbar
2	x	2,5 mm ²	1	x	2,5 mm ²	or busbar
2	x	4 mm ²	1	x	4 mm ²	or busbar
2	x	6 mm ²	1	x	6 mm ²	or busbar
2	x	10 mm ²				busbar
1	x	16 mm ²				busbar
1	x	25 mm ²				busbar


¹ Valid for ABB crimpage tool FER9500, FER9501 and ERG4

MCBs technical details

Terminal capacity of S200, S200M, S200MUC, S300P

Flexible cable with ferrule with collar


Stripping length 10...12mm, max terminal capacity¹



Conductor terminal			Busbar terminal			
2	x	0,75 mm ²	2	x	0,75 mm ²	or busbar
2	x	1 mm ²	2	x	1 mm ²	or busbar
2	x	1,5 mm ²	2	x	1,5 mm ²	or busbar
2	x	2,5 mm ²	1	x	2,5 mm ²	or busbar
2	x	4 mm ²	1	x	4 mm ²	or busbar
2	x	6 mm ²	1	x	6 mm ²	or busbar
1	x	10 mm ²				busbar
1	x	16 mm ²				busbar
1	x	25 mm ²				busbar

Flexible cable with twin-ferrule with collar

Stripping length 10...12mm, max terminal capacity¹



Conductor terminal			Busbar terminal			
(2)	x	0,75 mm ²	(2)	x	0,75 mm ²	or busbar
(2)	x	1 mm ²	(2)	x	1 mm ²	or busbar
(2)	x	1,5 mm ²	(2)	x	1,5 mm ²	or busbar
(2)	x	2,5 mm ²	(2)	x	2,5 mm ²	or busbar
(2)	x	4 mm ²	(2)	x	4 mm ²	or busbar
(2)	x	6 mm ²	(2)	x	6 mm ²	or busbar
(2)	x	10 mm ²	(2)	x	6 mm ²	or busbar

(2) means two conductors in one twin ferrules

¹ Valid for ABB crimpage tool FER9500, FER9501 and ERG4